

Technical specifications

Compatible hubs	All Ajax Hubs with OS Malevich 2.7 firmware
Compatible range extenders	All Ajax radio signal range extenders
False alarm prevention	Available, in the panic mode (long and short presses)
Number of buttons	1
Alarm delivery time	Not longer than 0.15 s Active from the first click (no need to wake it up)
Adjustable event types	Intrusion Fire Auxiliary alarm Panic button Gas alarm Malfunction Leakage Custom

If the custom type of the event is selected, event notifications will not be sent to the security company monitoring station and in an SMS to system users.

Jeweller radio technology	Communication range with a hub up to 1,300 m in an open space Two-way communication channel
Radio frequency bands:	866.0 – 866.5 MHz 868.0 – 868.6 MHz 868.7 – 869.2 MHz 905.0 – 926.5 MHz 915.85 – 926.5 MHz 921.0 – 922.0 MHz (depends on the sales region)

Maximum effective radiated power (ERP) up to 20 mW
Block encryption with a dynamic key
Radio frequency hopping

Power supply	Battery: CR2032 battery, 3 V ₌₌
Battery life	Up to 5 years
Operating temperature range	From -10°C to +40°C
Operating humidity	Up to 75%

Protection class	IP55
Dimensions	47 × 35 × 13 mm
Weight	16 g
Warranty	24 months
Complete set	Button CR2032 battery (pre-installed) Double-sided tape Quick Start Guide